

Diffused (sanblasted glass)




MINIATURIZATION IS OFTEN SEEN AS AN ALL-AROUND PROGRESS IN DESIGN, BUT EQUALLY OFTEN THE SIZE REDUCTION UNFORTUNATELY TURNS OUT TO ALSO BE A REDUCTION IN PERFORMANCE. FRANCESCONI, HOWEVER, DOESN'T DISAPPOINT WITH BRICK, A MINIMALIST YET DEFINED LUMINAIRE THAT'S VERY VERSATILE AND EASY TO INSTALL. BRICK ALSO HAS A MINIMAL IMPACT ON THE ARCHITECTURE IT ILLUMINATES.



- 1 anthracite
- 2 white RAL 9010
- 4 grey RAL 9006
- 8 dark brown

TECHNICAL SPECIFICATIONS

- Die casted EN AB46100 aluminum housing.
- High-resistance double painting process (UNI ISO9227:2012 saline test compliant).
- A4 stainless steel sealing allen screws.
- Extra clear tempered glass screen.
- Single-cable input, brass cable blocker IP66 for unipolaire cables.
- EPDM gasket.
- Compliant EN60598-1 and related annex.
- Working temperature: Ta Min: -20°C Max: +50°C



● FINISH

grey RAL 9006 gloss 6-10

■ LED COLOR

2700K

▲ BEAM

Diffused (sanblasted glass)

DETAILS

Light source:	LED
LED:	2700K
CRI:	70 (in accordance to EN62717)
Step MacAdam:	3
L90 Lifetime (Ta 35°):	70.000 hrs
W Led (real):	14.0
Lumen Tc 70° (real):	1814

Nominal Voltage:	220-240V 50/60Hz
Power supply:	Driver integrated INCLUDED ON/OFF
Class:	I
Cable:	Single input-None
Cable length:	None


IP:	IP65
IK:	08 (in accordance to IEC/EN62262)
Energy label:	A / A+ / A++

Warranty:	3 years, on request 5 years warranty extension
-----------	--

It is recommended to separate the LED board from the product to provide for the correct differentiated disposal of all components. The flow and power values are subject to tolerances. The images are only indicative.

ACCESSORIES AVAILABLE

A0009



CUSTOM TAB (SPECIFY THE
CUSTOM GRAPHIC ALONG WITH
THE ORDERS)