

ARCHILED 200 M (it.170430)



Hi Power wash LED Monochromatic fixture. 42 Hi-Power warm, neutral or cool white LEDs. On request: red, green, blue or amber. Touch control panel. IP 67 protection rating. Dimmable version RDM-DRS.

Technical Specification

LED type	WHITE 2700 K WHITE 3000 K WHITE 4000 K WHITE 6500 K RED GREEN BLUE AMBER
Lumen MAX	9000
Lenses	8° 15° 15°x30° 25° 40° 60°
Filters	None f 60° f 100° f 8°x 60°
Connectors and cables	Main Power: 3x1mm cable H05 1,5mt DMX signal: IN/OUT cable 0,3mt. + 4pin connectors IP67 (male-female)
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)
Functions	LED display with flip function DMX or Auto Mode with Master-Slave function Intelligent temperature control Continuous dimming 0-100% Smooth dimming function Halogen simulation CYM simulation Flicker-free function
Setup	RDM/DRS + touch control panel

DMX channels	3ch - 1ch
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	75
IP protection rating	67
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	270 x 100 x 303
Weight (Kgs)	5
Materials	Ultra clear 4mm tempered glass PMMA lenses Aluminium alloy housing Polyester powder coated
Mounting systems	Surface Truss (optional)
Colour finishing	Black RAL 9005 (standard) Grey RAL 9006 (optional) White RAL 9010 (optional)
Marine Grade treatment	None Yes
Product Category	Spot
Accessories - Flight case	None Yes
Accessories - Anti glare	None Yes
Accessories - Barn door	None Yes

Your Configuration

LED type	WHITE 2700 K
Lumen MAX	9000
Lenses	8°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	75
IP protection rating	67
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	270 x 100 x 303
Weight (Kgs)	5
Mounting systems	Surface
Colour finishing	Black RAL 9005 (standard)
Marine Grade treatment	None
Product Category	Spot
Accessories - Flight case	None
Accessories - Anti glare	None
Accessories - Barn door	None