

MPCOLOR 96 RGBW (it.194010)



Wash/flood light fixture with 12 independent segment control 8 LEDs, which can be controlled individually to create engaging eye candy that enhances any live production. IP 65 protection rating. RDM/DRS.

Technical Specification

LED type	RGBW5050MULTICHIP
Number of LEDs	96
LED expected lifetime (hrs)	50000
Lumen MAX	71808
Red lumen (lm)	15360
Green lumen (lm)	26880
Blu lumen (lm)	4800
White lumen (lm)	29568
Colour temperature range (K)	2000 - 10000
Lenses (upper head)	8° 15° 15° x 30° 25° 40° 60°
Lenses (lower head)	8° 15° 15° x 30° 25° 40° 60°
Filters (upper head)	None f 60° f 100° f 8°x 60° frost 65°

Filters (lower head)	None f 60° f 100° f 8°x 60° frost 65°
Connectors and cables	Main Power: PowerCon IP65 connector (male-female) DMX signal: XLR5pin IP65 connector (male-female)
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)
Functions	LED display with flip function Dedicated DMX channel for white balance from 2000K to 10000K Dedicated DMX channel for macro DMX or Auto Mode with Master-Slave function Intelligent temperature control Smooth dimming function Ultrafast strobe effect Halogen simulation CYM simulation Flicker-free function
Setup	RDM/DRS + touch control panel
DMX channels	54ch - 48ch - 9ch - 4ch
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	900
Current	4A@230VAC
Power Factor	PF>0,95@230VAC
Inrush current	60A@230V
IP protection rating	65 67 optional
Sizes l x p x h (mm)	672 x 204 x 569mm
Weight (Kgs)	30
Materials	Ultra clear 4mm tempered glass PMMA lenses Aluminium alloy housing Polyester powder coated
Mounting systems	Surface Truss (optional)
Colour finishing	Black RAL 9005 (standard) Grey RAL 9006 (optional) White RAL 9010 (optional) Any RAL (optional)
Marine Grade treatment	None Yes
Product Category	Wall Washer
Accessories - Handle	None Yes

Accessories - Flight case	None Yes
Accessories - Anti glare	None Yes
Accessories - Barn door	None Yes

Your Configuration

LED type	RGBW5050MULTICHIP
Number of LEDs	96
LED expected lifetime (hrs)	50000
Lumen MAX	71808
Red lumen (lm)	15360
Green lumen (lm)	26880
Blu lumen (lm)	4800
White lumen (lm)	29568
Colour temperature range (K)	2000 - 10000
Lenses (upper head)	8°
Lenses (lower head)	8°
Filters (upper head)	None
Filters (lower head)	None
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	900
Current	4A@230VAC
Power Factor	PF>0,95@230VAC
Inrush current	60A@230V
IP protection rating	65
Sizes l x p x h (mm)	672 x 204 x 569mm
Weight (Kgs)	30
Mounting systems	Surface
Colour finishing	Black RAL 9005 (standard)
Marine Grade treatment	None
Product Category	Wall Washer
Accessories - Handle	None
Accessories - Flight case	None
Accessories - Anti glare	None
Accessories - Barn door	None