

TERRA WL5 POB M (it. 210310)



On-board power supply IP 67 stainless steel AISI 304 inground lighting fixture suitable for outdoor installations. It includes n.5 x 10W Monochromatic LEDs. DMX-RDM-DRS version.

Technical Specification

LED type	WHITE 2700 K WHITE 4000 K WHITE 6500 K RED GREEN BLUE AMBER
Number of LEDs	10
Lumen MAX	2500
Lenses	8° 15° 15°x30° 25° 40° 60°
Filters	None f 17° tilt f34° tilt f 60° f 65° f 100° f 8°x 60°
Connectors and cables	Main Power: 3x1mm cable H05 1,5mt DMX signal: IN/OUT cable 0,3mt. + 4pin connectors IP67 (male-female)
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)
Functions	DMX or Auto Mode with Master-Slave function Intelligent temperature control Continuous dimming 0-100% Smooth dimming function Halogen simulation Flicker-free function

Setup	RDM/DRS
DMX channels	3ch - 1ch
Input range	100 - 277 VAC; 47/63 Hz
Power (W)	18
IP protection rating	67 68 optional
IK grade protection	08
Dimensions d x h (mm)	190 x 74,6
Weight (Kgs)	4
Materials	Ultra clear 10mm tempered glass
Mounting systems	Inground
Product Category	Inground
Case	AISI 304 (standard) AISI 316 (optional) Aluminium (optional) Aluminium - Marine Grade (optional)

Your Configuration

LED type	WHITE 2700 K
Number of LEDs	10
Lumen MAX	2500
Lenses	8°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 277 VAC; 47/63 Hz
Power (W)	18
IP protection rating	67
IK grade protection	08
Dimensions d x h (mm)	190 x 74,6
Weight (Kgs)	4
Mounting systems	Inground
Product Category	Inground
Case	AISI 304 (standard)