

PIN LIGHT M (it.160540)



Technical Specification

LED type	WHITE 2700 K WHITE 4000 K WHITE 6500 K RED GREEN BLUE
Number of LEDs	1 (5W) White (Warm, Neutral, Cool)
Lenses	1,5° Ultra Narrow
Control type	External Control Driver Protocol USITT DMX512 - RDM
Functions	RDM/DRS
Input range	100 - 277 VAC; 47/63 Hz
Power (W)	5
IP protection rating	IP 67
Sizes l x p x h (mm)	98 x 133 x 79,5
Weight (Kgs)	0,7
Mounting systems	Surface Truss (optional)
Colour finishing	Grey RAL 9006 (standard) Black RAL 9005 (optional) White RAL 9010 (optional)
Marine Grade treatment	None Yes
Product Category	Ultra Narrow Beam

Your Configuration

LED type	WHITE 2700 K
Number of LEDs	1 (5W) White (Warm, Neutral, Cool)
Lenses	1,5° Ultra Narrow
Control type	External Control Driver
Input range	100 - 277 VAC; 47/63 Hz
Power (W)	5
IP protection rating	IP 67
Sizes l x p x h (mm)	98 x 133 x 79,5
Weight (Kgs)	0,7
Mounting systems	Surface
Colour finishing	Grey RAL 9006 (standard)
Marine Grade treatment	None
Product Category	Ultra Narrow Beam